

OP

OMAN PLASTER

- ◆ **Dash Coats**
- ◆ **Cement Renders/Plasters**
- ◆ **Decorative Colour Renders**
- ◆ **Gypsum Plasters**
- ◆ **Masonry mortars**
- ◆ **Floor screeds**
- ◆ **Concrete repair mortars**
- ◆ **Non shrink grouts**
- ◆ **Thermo renders**
- ◆ **Thermo Adhesives**



www.omanplaster.com

COMPANY PROFILE



Oman Plaster (OP) - A leading manufacturer of dry mix products with its manufacturing facility located in Sohar Industrial Estate, Sultanate of Oman. Oman Plaster (OP) offers its customers wide range of products and services to meet up the fast growing and challenging demands of the construction industry in Oman. Oman Plaster (OP) is unique by offering its customers superior products and services. Our goal is to achieve highest customer satisfaction through the quality, reliability and consistency of our products and services. Our product range covers pre-blended dry mix products based on Cement and Gypsum.



Oman Plaster (OP) offers the most modern silo system with pneumatic dry mix conveying and automatic application machines for the construction industry. Pre-blended factory produced dry mix mortar are much more superior and reliable than site mixed mortars. Each product is accurately produced and tested to ensure the quality. We offer the product delivery to the site in silos or bags. A range of machines are available for the various applications of the products at site. Oman Plaster (OP) provides the world class application machines from PFT, Germany. The dry mix product application with machine ensures the homogeneous and accurate mixing with water, thus eliminating the errors hazards associated with the manual mixing. The products are delivered to any distance in time with silos and pneumatic conveying system. The system will provide the customers a clear edge in terms of superior quality and productivity.



Oman Plaster (OP) silo system with the pneumatic dry mix conveying will provide a clean and dust free job site adding more value to health, safety and environment.

Oman Plaster (OP) products are designed and manufactured meeting the specifications of BS/EN/DIN/ASTM standards. Our most modern state-of-the-art manufacturing facility and stringent quality control measures will ensure the superior quality for the products. We have a fully equipped in-house laboratory for the quality checks. Oman Plaster (OP) will be assuring the superior quality of its products by strict quality checks starting from the selection of raw material to the finished products. We are technically expertise and equipped for the design, develop and manufacture of custom made products meeting the specific requirements of our valued customers.

Our expertise team of sales/QC/site engineers will provide the customers total support as and when required.

Oman Plaster (OP) offers a wide products range of Dash Coats , Cement Plasters/Renders , Decorative Colored Renders , Insulation Renders & Adhesives , Gypsum Plasters, Masonry Mortars, Tile Adhesives, Floor Screeds, Repair Mortars , Non Shrink Grouts etc.....


Oman Plaster (OP) offers its products delivery to the site in 25-50 kg paper bags stacked in wooden pallets with plastic shrink wrap or 20 m³ mobile silos which can be placed at site in a convenient position.



Benefits of Oman Plaster (OP) system

- Superior quality & consistency through out the project
- Save time and man power
- Accurately pre blended dry mix requires only the addition of water at site
- Environment friendly, clean and healthy job site
- Material protected from weather, spillage and theft
- Ease of the application resulting in more out put
- World class machines and tools for the application

OMAN PLASTER PRODUCT LIST

Products	Application Details	Packing	Approx Coverage [per tonne]
Dash Coat OP2100	Dash coat material to achieve good key for rendering on normal fair faced concrete surfaces. Application by tyrolean box/ spray hopper @ 2-5mm.	 50kg Bags	430 m ² @ 2mm thickness
Dash Coat OP2120	Dash coat material to achieve good key for rendering on densified concrete surfaces. Application by tyrolean box/ spray hopper @ 2-5mm.	 50kg Bags	430 m ² @ 2mm thickness
Dash Coat OP2140	Dash coat material to achieve good key for rendering on ultra smooth concrete surfaces. Application by tyrolean box/ spray hopper @ 2-5mm.	 50kg Bags	430 m ² @ 2mm thickness
Dash Coat OP2150	Dash coat material to achieve good key for rendering on impermeable/non absorbing surfaces (EPS/XPS etc). Application by tyrolean box/ spray hopper @ 5-6mm.	 50kg Bags	430 m ² @ 2mm thickness
Cement Plaster/Render OP2200	Plaster/render for internal/external concrete block walls. Application by spray machine/manual @ 10-20mm.	 12-20 m ³ OP Silo 50kg Bags	42 m ² @ 15mm thickness
Cement Plaster/Render AAC/Concrete OP2210	Plaster/render for internal/external AAC/concrete block walls. Application by spray machine/manual @ 10-20mm.	 12-20 m ³ OP Silo 50kg Bags	42 m ² @ 15mm thickness
Cement Render OP2230	Render for external plinth areas. Application by spray machine/manual @ 15-20mm.	 12-20 m ³ OP Silo 50kg Bags	30 m ² @ 20mm thickness
Cement Plaster/Render OP2240	Plaster/render for high strength (> 15 MPa) requirements. Application by spray machine/manual @ 15-50mm.	 12-20 m ³ OP Silo 50kg Bags	37 m ² @ 15mm thickness
Cement Plaster OP2250	Fine thin coat plaster for ceilings and rough cement plaster surfaces. Application by spray machine/manual @ 4-6mm.	 12-20 m ³ OP Silo 50kg Bags	162 m ² @ 4mm thickness
Decorative Colour Render OP2300	Decorative colour render for external block walls. Application by spray machine/manual @ 15-20mm.	 12-20 m ³ OP Silo 50kg Bags	42 m ² @ 15mm thickness
Decorative Colour Render OP2310	Decorative textured color render for external block walls. Application by spray machine/manual @ 15-20mm.	 12-20 m ³ OP Silo 50kg Bags	35 m ² @ 15mm thickness
Render for rock work OP2320	High strength (> 15 MPa) decorative textured color render for landscaping works. Application by spray machine/manual @ 15-50mm.	 12-20 m ³ OP Silo 50kg Bags	38 m ² @ 15mm thickness
Gypsum Plaster OP2400	Standard gypsum plaster for internal AAC/concrete block walls. Application by spray machine/manual @ 10-20mm.	 12-20 m ³ OP Silo 25kg Bags	58 m ² @ 12mm thickness

OMAN PLASTER PRODUCT LIST

Products	Application Details	Packing	Approx Coverage [per tonne]
Gypsum Plaster OP2410	Fine thin coat gypsum plaster for ceilings and rough cement plaster surfaces. Application by spray machine/manual @ 4-6mm.	 12-20 m³  25 kg	208 m² @ 4mm thickness
Gypsum Plaster OP2412	Fine thin coat gypsum plaster for direct application on concrete surfaces. Application by spray machine/manual @ 4-6mm.	 12-20 m³  25 kg	208 m² @ 4mm thickness
Masonry mortar for concrete blocks OP2500	Block laying mortar for concrete masonry block works. Mixing by screw machine/manual.	 12-20 m³  50kg	36 m² @ 10mm thickness
Masonry mortar for AAC blocks OP2510	Block laying mortar for AAC masonry block works. Mixing by screw machine/manual.	 12-20 m³  50kg	82 m² @ 5mm thickness
Tile Adhesive OP2552	Tile fixing adhesive for ceramic tiles on internal /external areas. Mixing by screw machine/manual.	 50kg	Yield 685 L/ton
Tile Adhesive OP2554	Tile fixing adhesive for ceramic/porcelain/glass tiles on internal/ external areas. Mixing by screw machine/manual.	 50kg	Yield 670 L/ton
Floor Screed (15 MPa-40 MPa) OP2600	Bonded/un bonded/floating leveling screed for floors. Mixing by screw machine/manual.	 12-20 m³  50kg	Yield 530 L/ton
Repair Mortar OP2700	Fine repair mortar for concrete surfaces. Mixing by screw machine/manual.	 50kg	Yield 620 L/ton
Repair Mortar OP2710	Thick repair mortar for concrete surfaces. Mixing by screw machine/manual.	 50kg	Yield 530 L/ton
Non-shrink grout OP2800	Non-shrink grouting mortar for medium strength (40 MPa) anchoring applications. Mixing by screw machine/manual.	 12-20 m³  50kg	Yield 510 L/ton
Non-shrink grout OP2810	Non-shrink grouting mortar for high strength (70 MPa) anchoring applications. Mixing by screw machine/manual.	 12-20 m³  50kg	Yield 510 L/ton
Thermo render OP2900	Thermal insulation render for external walls (λ = 0.1 W/m.K). Application by spray machine @ 40-60mm.	 12-20 m³  50kg	48 m² @ 40mm thickness
Thermo adhesive OP2910	Thermo adhesive for EPS/XPS thermal insulation sheets. Mixing by screw machine/manual.	 50kg	200 m² @ 3mm thickness



conveying and mixing system with silos



OMAN PLASTER L.L.C

P.O.Box: 537, Postal code: 322
Sohar Ind. Estate, Sohar, Sulthanate Of Oman

Office Tel: (+968) 26 70 1686, Office Fax: (+968) 26 70 16 88
E-mail: op@omanplaster.com, Website: www.omanplaster.com